

# BR100 Router

## Branch Router with built-in 802.11n



The **Aerohive Networks BR100** router marries 802.11n performance, enterprise security, and advanced wired/wireless management with cloud computing to deliver a zero-touch branch network deployment.

“Work anywhere” mobility meets enterprise routing and security in a compact device. With HiveOS Routing at its core, the BR100 includes IPsec VPN, user-based access control, and fully stateful firewall policies, as well as additional security and RF networking features at no extra cost; all without the need for a centralized or dedicated controller. Combining these award-winning capabilities with cloud-based services allows the BR100 to meet your budgetary requirements and blow past your remote workers’ expectations.

### Key Features and Benefits

#### Layer 3 IPsec VPN and Flow-based Stateful Firewall

By using device-based IPsec VPN, HiveOS Routing features on every BR100, allows a remote users to access corporate resources via authenticated devices without the hassle of installing configuring or maintaining additional VPN software. In addition, an advanced flow-based stateful firewall enforces policy on a per data flow basis allowing the Aerohive device to manage traffic via a combination of user identity and very granular mobile device type. A user can now be granted secure access to corporate resources based on both who they are and on the type of device that they are using, providing an invaluable additional level of security regardless of the users’ location.

#### Wired/Wireless Access and Control

The BR100 includes 5 Ethernet switch ports, a single 802.11 b/g/n radio, a USB port for 3G/4G WAN backup, and a power adaptor. Since HiveManager manages the device’s identity, the security and network access policy is the same regardless of whether the clients are connecting via wireless or wired ports.

#### Cloud Proxy

Cloud-based security services ensure that branch office communications are “clean” without requiring that IT run additional security appliances at every branch office or configure web proxy information on every end user’s device. Since most of the traffic generated at branch or remote locations is destined for the Internet, Aerohive’s patent-pending Cloud Proxy automatically diverts that traffic through a cloud-based web security service, vastly reducing bandwidth costs by eliminating the need to route branch, remote office or mobile-user traffic back to a central location for filtering.

#### Access That Grows With Your Business

As businesses grow so do the number of branches. The BR100 runs the same HiveOS that runs on all our products, which means that as your branches grow the BR100 can leverage Aerohive’s Cooperative Control Architecture and mesh functionality to add wireless coverage to the branch locations as well. Simply install an additional HiveAP access point and the BR100 will form a wireless mesh connection with it. Within minutes your new access point will download your security policies and your secure wireless coverage will be expanded. For more, visit [www.aerohive.com/products](http://www.aerohive.com/products).

### Warranty and Support

Every Aerohive Networks device is backed by a limited lifetime hardware warranty. Extended product and technical support may be purchased separately and can include next day advanced replacement, 24x7 or 8x5 technical support, web and email support access, and software updates. For complete support terms go to [www.aerohive.com/support](http://www.aerohive.com/support).

[Contact us today](#) to learn how your organization can benefit from Aerohive networking solutions.



### Aerohive Networks, Inc.

330 Gibraltar Drive  
Sunnyvale, California 94089 USA  
phone 408.510.6100  
toll-free 866.918.9918  
fax 408.510.6199  
[www.aerohive.com](http://www.aerohive.com)

## Product Specifications

### Mounting

- Desktop
- Keyhole Wall Mounts

### Wi-Fi

- 1x1 Single Band 802.11b/g/n

### Data Rates

- 802.11b: 1,2,5,5 and 11Mbps
- 802.11g: 6,9,12,18,24,36,48, and 54 Mbps
- 802.11n (HT20/HT40): MCS0 -MCS7

### Frequency Band

- 2412MHz - 2472MHz Frequency Band

### Modulation

- BPSK, QPSK, 16QAM, 64QAM, DQPSK and CCK

### Encryption

- WEP, AES and TKIP

### Antennas

- 2x embedded antenna with diversity function

### Interfaces

- 1x IEEE 802.3 (10BASE-T) and IEEE 802.3u(100BASE-TX) Compliant 10/100 Mbps RJ45 Fast Ethernet WAN Port
- 4x IEEE 802.3(10Base-T) and IEEE802.3u(100BASE-TX) Compliant 10/100Mbps RJ45 LAN Ports with auto-sensing and auto-MDI/MDI-X, IEEE 802.3x PAUSE frame flow control in full duplex
- 1x Type-A USB2.0 port backward compatible with USB1.1
- 1x Reset button to reset (on press) and load factory default settings (when pressed for more than 5 seconds)

### Modem Support

- US/NAM Modules
  - Sierra Wireless 313U
  - Sierra Wireless 308U
  - Pantech UML 290
  - Novatel 551L
- International Modems
  - Sierra Wireless 310U
  - Sierra Wireless 312U
  - Sierra Wireless 319U
  - Sierra Wireless 320U
  - Sierra Wireless 326U
  - Huawei E220
  - Huawei E1752
  - Huawei UMG366
- Additional modems on roadmap\*

### LEDs

- Power/Status • WAN Port • LAN Ports (1-4)

### Physical

- 134 x 109 x 30 mm

### Security

- 1 Kensington Lock Connector

### Environmental

- Operating: 0 to +40°C, Storage: -20 to +70°C
- Humidity: 5 to 95% RH (non-condensing)

### MTBF

- >200,000 hours based on Telecordia SR-332, Issue 2 at +25°C ambient temperature

### Power

- DC 12V/1A Input

| Rate               | TX Power (dBm) | RX Sensitivity |
|--------------------|----------------|----------------|
| <b>Legacy Mode</b> |                |                |
| 1 Mbps             | 18             | -95            |
| 11 Mbps            | 18             | -88            |
| 6 Mbps             | 18             | -93            |
| 54 Mbps            | 18             | -76            |
| <b>HT20 Mode</b>   |                |                |
| MCS0               | 18             | -92            |
| MCS7               | 14             | -72            |
| <b>HT40 Mode</b>   |                |                |
| MCS0               | 16             | -88            |
| MCS7               | 15             | -69            |

## Features & Benefits

### Cooperative Control Software

- Supports HiveOS 5.0r1 and later releases
- Automatic Mesh with Aerohive APs
- User identity and device type (network MDM controlled access to networks)

### Flexible Hardware Platform

- Single 802.11b/g/n radio
- Automatic or dedicated mesh backup

### Security

- Wireless privacy & authentication Wi-Fi CERTIFIED™ WPA™ and WPA2™, 802.11i, WEP, 802.1x, PSK, PPSK
- Granular user profile-based management defines QoS, mobility policies, and security policies for each user and device type that enters the network

- Wired authentication including 802.1X, MAC authentication, and Captive Web Portal support
- Encryption: AES-CCMP, TKIP, and RC4 (WEP only)
- Marking and policing-WMM™ (802.11e) for wireless, 802.1p and/or DiffServ
- Priority queuing for Voice packets on wired interfaces
- Wi-Fi CERTIFIED WMM
- WMM power save (U-APSD)
- Device registration codes for secure, zero-touch auto-configuration
- Dual WAN Redundancy (USB and Ethernet)
- Policy-based Route load balancing with active-active WAN support
- Ability to operate in AP or Router mode

| Features                       | Platforms     |                |                |
|--------------------------------|---------------|----------------|----------------|
|                                | BR100         | BR200          | BR200-WP       |
| <b>General</b>                 |               |                |                |
| Recommended Users              | 1 to 10       | 1 to 50        | 10 to 50       |
| FW/VPN Mbps                    | 5-10 Mbps     | 75Mbps         | 75Mbps         |
| Radio                          | 1 1x1 11bgn   | None           | 1 3x3:3 11abgn |
| Interfaces                     | 5x 10/100     | 5x 10/100/1000 | 5x 10/100/1000 |
| Managed PoE                    | None          | None           | 2 PoE PSE      |
| SNMP                           | None          | Yes            | Yes            |
| USB WAN as Primary             | Yes           | Yes            | Yes            |
| SSIDs                          | 4             | 0              | 16             |
| Networks                       | 4             | 16             | 16             |
| User Profiles                  | 32            | 64             | 64             |
| <b>Wi-Fi</b>                   |               |                |                |
| Wi-Fi Client Max Mbps          | 135Mbps       | N/A            | 450Mbps        |
| Spectrum Analysis              | No            | N/A            | Yes            |
| Wi-Fi as WAN                   | No            | N/A            | Yes            |
| WIPS                           | Basic Rogue   | N/A            | Yes            |
| WPA2-PSK                       | Yes           | N/A            | Yes            |
| WPA2-802.1X                    | Yes           | Wired Only     | Yes            |
| PPSK SSID Support              | Yes           | N/A            | Yes            |
| <b>Security and Management</b> |               |                |                |
| RADIUS Server/Proxy            | external only | Yes            | Yes            |
| AD Integration                 | external only | Yes            | Yes            |
| PPSK Server                    | Yes           | No             | Yes            |
| Cloud Proxy                    | Yes           | Yes            | Yes            |
| <b>Voice</b>                   |               |                |                |
| Voice QoS                      | Yes           | Yes            | Yes            |
| Access Port Based Voice        | Yes           | Yes            | Yes            |
| Trunk Port Based Voice         | No            | Yes            | Yes            |

| SKU                           | Description                                                                                             |
|-------------------------------|---------------------------------------------------------------------------------------------------------|
| <b>Aerohive Branch Router</b> |                                                                                                         |
| AH-BR-100-N-FCC               | BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, FCC regulatory domain, with power supply                       |
| AH-BR-100-N-W                 | BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, configurable regulatory domain, with power supply              |
| AH-BR-100-N-FCC-20PK          | Quantity 20: BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, FCC regulatory domain, with power supply          |
| AH-BR-100-N-W-20PK            | Quantity 20: BR100, 4xFE, 1xWAN, 1 radio 802.11b/g/n, configurable regulatory domain, with power supply |
| <b>BR Accessories</b>         |                                                                                                         |
| AH-ACC-PWR-12W-US             | 12W power supply and US power plug for BR100                                                            |
| AH-ACC-PWR-12W-EU             | 12W power supply and EU power plug for BR100                                                            |
| AH-ACC-PWR-12W-UK             | 12W power supply and UK power plug for BR100                                                            |
| AH-ACC-PWR-12W-AU             | 12W power supply and AU power plug for BR100                                                            |